

JX STRADDLE SERIES

56 - 66 HP



High capacity front-end axle for loader operations up to 3500kg.

Superb crop clearance for crops of all types to provide exceptional versatility.

Dry air filter ensures long service intervals while coping with difficult, dusty conditions.

Shuttle Forward/Reverse provides easy to operate, versatile power and loading operations.

JX STRADDLE - TOUGHNESS COMES STANDARD

Demand more from your equipment. Case IH tractors are engineered from the ground up to deliver reliable and durable performance. The Case IH JX Straddle combines the strength and power you need in demanding applications. Heavy duty components ensure a long operating life and reduced downtime so you can get the job done properly. **Case IH JX Straddle - heavy-duty, high-powered and professional equipment.**

Separate Steering and Main Hydraulic Pump.

Maintain full hydraulic power to implements even under loads giving exceptional productivity.

Dry Air Filter For High Service Intervals.

Service is only required at 300 hours, ensuring more time working in the field.

Fast Raise/Lower Hitch with Preset Weight Control.

Raise and lower the hitch to the exact height with just one push of a button for fast output.

Professional Series Engine and Transmission for Long Life.

Maintain the greatest resale value with quality components and durable parts.

12/4 Transmission with Shuttle Reversing.

Left hand shuttle controls speed up slashing and loader work and reduces your work.

Large Tyres For Stability and Ground Protection.

30" rear wheel equipment lessens soil compaction and results in less surface damage.

Tight turning circle provides excellent maneuverability in narrow rows.

Water-cooled 3-cylinder diesel tuned for low fuel use and power output of 203g/kwh.



JX STRADDLE SERIES 56 - 66HP



Reliable Equipment For Professional Agriculture

The JX Straddle tractor from Case IH is manufactured to the same stringent quality standards that you would expect from Case IH. Its heavy duty components set the JX Straddle apart from its peers and provide your business with the value and performance required year after year.





B100 Compatible

| MODEL | JX60 STRADDLE | JX70 STRADDLE | JX80 STRADDLE |
|---|------------------------|------------------------|------------------------|
| ENGINE | | | |
| No of cylinders | 3 cyl NA | 3 cyl TC | 4 cyl NA |
| Displacement [CM3] | 2931 | 2931 | 3908 |
| Power 2000/25/EC (HP[CV]/KW) @ 2500 RPM | 56 hp / 41 kW | 66 hp / 49 kW | 75 hp / 56 kW |
| Max Torque [Nm] at 1500 rpm / Torque Rise % | 198 / 27% | 255 / 38% | 274 / 26% |
| PTO Power [hp (CV) / kW] | 44 / 36 | 54 / 40 | 65 / 48 |
| Optimum fuel consumption [gr/Kwh] | 203 | 203 | 205 |
| Fuel tank capacity [litres] | 77 | 77 | 77 |
| Exhaust | Underhood muffler | Underhood muffler | Underhood muffler |
| TRANSMISSION | | | |
| Type standard | Mechanical | Mechanical | Mechanical |
| No of speeds | 12x4 | 12x4 | 12x4 |
| Gearbox features | Constant Mesh | Constant Mesh | Constant Mesh |
| Synchronisation type | All speeds Synchronesh | All speeds Synchronesh | All speeds Synchronesh |
| Location of control levers | 2, central | 2, central | 2, central |
| Rear diff lock | Mechanical | Mechanical | Mechanical |
| PTO | | | |
| PTO clutch | Mech / 1 lever | Mech / 1 lever | Mech / 1 lever |
| PTO features | Fully independent | Fully independent | Fully independent |
| PTO speeds | 540rpm | 540rpm | 540rpm |
| PTO shaft type | 1/38" - 6 splineshaft | 1/38" - 6 splineshaft | 1/38" - 6 splineshaft |
| HYDRAULICS | | | |
| Steering pump | 26.5l/min | 26.5l/min | 26.5l/min |
| Centre system | Open | Open | Open |
| Flow output (L/M) / Max pressure (bar) | 40.1L / Min / 190 bar | 40.1L / Min / 190 bar | 40.1L / Min / 190 bar |
| Remotes | 1 Double Acting | 2 Double Acting | 2 Double Acting |
| DIMENSIONS | | | |
| Wheelbase 2WD (MM) | 2118 | 2118 | 2248 |
| Wheelbase 4WD (MM) | 2062 | 2062 | 2192 |
| Min shipping weight 2WD Rops (KG) | 2320 | 2320 | 2650 |
| Min shipping weight 4WD Rops (KG) | 2560 | 2560 | 3080 |
| Max Permissible Weight | 5400 | 5400 | 5800 |
| Ground clearance 4WD (MM) | 340 | 365 | 390 |
| Ground clearance rear (MM) | 340 | 340 | 340 |
| HITCH | | | |
| Hitch Type | Cat II Ball End | Cat II Ball End | Cat II Ball End |
| Lift Capacity @ 610mm (kg) Full Range | 2260 | 2260 | 2700 |

Safety never hurts! Always read the Operator's Manual before working with any equipment. Inspect equipment before using it, and be sure it is operating properly. Follow the product safety signs, and use any safety features provided. This literature has been published for worldwide circulation. The standard and optional equipment and the availability of individual models may vary from one country to the next. Case IH reserves the right to undertake modifications without prior notice to the design and technical equipment at all times without this resulting in any obligation whatsoever to make such modifications to units already sold. Whilst every effort is made to ensure that the specifications, descriptions and illustrations in this brochure are correct at the time of going to press, these are also subject to change without prior notice. Illustrations may show optional equipment or may not show all standard equipment.